

WORKPLACE OPTIMIZATION

smartTOUCH Flex

Multifunctional Touchscreen



WHY WEYTEC

MORE THAN A TOUCHSCREEN
... flexible, expandable & adaptable

The multifunctional smartTOUCH Flex provides an intuitive user interface and virtually unlimited functionality. Combined with a standard keyboard and mouse, users can access, control and share all sources and screens. Monitors and video walls can be managed by a single touch. Operators can stream video and quickly execute application inputs with the touchscreen. The smartTOUCH Flex has a modular architecture and can be readily adapted to meet the unique requirements of control room environments.

- Easy and flexible usability with a modern 10.1" LCD touchscreen
- Compatible with any standard keyboard and mouse
- Extended functionality with individual applications
- Integrated loudspeakers
- Multiple interfaces to directly connect peripheral devices
- Display two movable and scalable windows (Picture-in-Picture)
- Robust and stable
- Adjustable angle of inclination between 15° - 64°

WHY WEYTEC

OPTIMAL

... freedom of design at the workplace

The multifunctional smartTOUCH Flex enhances flexibility at the workplace and on the desk. It can be used with any standard keyboard and mouse.

Touchscreen & Loudspeakers



The touchscreen provides a user-friendly interface to work with diverse systems. It displays all sources and monitors. Available sources are indicated in green, occupied sources in red and «view only» sources in white. Sources are easily selected and assigned to monitors and video walls. Switching between individual sources is simple using tabs.

Touchscreen functionality can be extended with individual applications. Almost anything is possible, from video integration, event visualization and telephony to enterprise-specific applications. Speakers integrated in the base reproduce an audio mix of all the sources.

Picture-in-Picture

Two movable and scalable windows from any two IP Remote sources can be activated, displayed and operated on the touchscreen. These can be video streams or other applications.

Interfaces

The smartTOUCH Flex supports a multitude of interfaces (USB transparent, USB for keyboard and mouse, Ethernet with PoE+, audio, etc.) as well as virtually any platform deployed in control room environments.



Angle of inclination

The angle of inclination can be adjusted in incremental steps between 15° - 64°.



Available Products

Article No.	Description
22002	smartTOUCH Flex

Specifications	Description
Power supply	PoE+, external power supply unit
Dimensions W/D/H (mm)	261x220x (min. 100 - max. 177)
Angle of inclination	ca. 15.9° - 64.6°
Display	10.1" LCD, 1280x800@60Hz